



Knurling wheels




Form knurling



AA




BL30°



BR30°



BL45°



BR45°

Knurling wheels, milled, with chamfer 45° – HSS

Standard variants	Profile		Dimensions [mm]			Pitch [mm]
			Ø	Width	Bore	
Nr. 08	AA		10	4	4	○
Nr. 08			15	4	4	○
Nr. 08			15	6	4	●
Nr. 08			20	8	6	●
Nr. 08	BL	30°	15	4	4	○
Nr. 08			20	8	6	●
Nr. 08	BR	30°	15	4	4	○
Nr. 08			20	8	6	●
Nr. 08	BL	45°	10	4	4	○
Nr. 08			15	6	4	○
Nr. 08	BR	45°	10	4	4	○
Nr. 08			15	6	4	○

Standard pitches / profile angle 90°

● 0,6/0,8/1,0/1,2/1,5

○ 0,6/0,8/1,0


Cut knurling



AA



BL30°



BR 30°

Knurling wheels, milled, without chamfer – HSS

Standard variants	Profile		Dimensions [mm]			Pitch [mm]
			Ø	Width	Bore	
Nr. 09	AA		15	4	8	□
Nr. 09			25	6	8	■
Nr. 09	BL	30°	15	4	8	□
Nr. 09			25	6	8	■
Nr. 09	BR	30°	15	4	8	□
Nr. 09			25	6	8	■

Standard pitches / profile angle 90°

■ 0,8/1,0/1,5

□ 0,8/1,0